BES3.5

3.5" TWO-WAY MONITOR SPEAKER

BES Series: Perfect for Personal Studios and Versatile Audio Applications!



Description

The BES series is Superlux's latest offering designed specifically for personal studios and multi-purpose audio applications, available in two options: 3.5-inch and 5-inch models.

The BES3.5 is a 3.5-inch two-way monitor system that includes one active and one passive speaker, combining high-accuracy sound quality with flexible connectivity options. Ideal for music production, video editing, and daily listening, the BES3.5 delivers exceptional sound detail, ensuring accurate reproduction across all frequencies. Its sleek design and durable construction make it a reliable choice for various environments.

With multiple connection options, including TRS and 1/8-inch inputs, the BES3.5 easily integrates with a wide range of audio devices. Additionally, it features high and low-frequency gain and attenuation controls to better adapt to different room environments and speaker placements.

Features

- 3.5" Woofer and 1" Tweeter: Delivers powerful, deep bass and crisp, clear highs, ensuring a balanced sound across the entire frequency range.
- 50-Watt Output Power: Perfectly suited for various audio needs, ideal for both desktop and near-field monitoring environments.
- Multiple Connectivity Options: Supports TRS and 1/8" inputs, effortlessly compatible with a wide range of audio devices.
- Rear Volume control: Convenient for users to quickly adjust volume, enhancing ease of use and overall experience.

Specifications

Crossover Frequency	3 KHz
Max. SPL	100 dB SPL
Frequency Response (-3 dB)	80 - 20 KHz
Impedance	10k Ω
LF	3.5 in.
HF	1 in. Cloth Diaphragm
Enclosure Material	Wood
Input Impedance	Bal: 1/4" TRS Unbal: RCA 1/8" Stereo
TRIM for HF	+3 dB / -3 dB
TRIM for LF	+3 dB / -3 dB
Output Power	50W
Ac Power	AC 100-240V 50-60 Hz
Dimensions	W150 × H226 × D180 mm (5.90 × 8.89 × 7.08 in.)
Net weight	4.3 kg (151.6 oz)